INDUSTRIAL FLOOR (AUTOHAUS SINGER)

# USE THE FIBROFOR HIGH GRADE MICROFIBRE








## OVERVIEW

| | |
|---|---|
| **PROJECT** | Showroom in the car dealership, D-876 |
| **PRODUCT** | High Grade 19 mm |
| **EXPANSE** | 485 m² |
| **REGION** | Bavaria (D-87) |
| **MISC** | on XPS insulation |

## PRODUCT FEATURES

For this construction project, the statically chargeable synthetic microfibre HIGH GRADE was used for a 20 cm thick industrial floor on XPS insulation (10 cm). The cut joint grid is 5 x 5 m in the interior area. The specially developed spliced fibre is suitable for low to medium loads. It has a positive influence on the shrinkage behaviour of the concrete, spreads very well in the concrete and can be worked into the surface optimally.

## ADVANTAGES

- Reinforcement construction is eliminated or reduced (cost and time saving)
- Structural design according to Eurocode 2
- Jointless surfaces up to 1.000 m²
- No corrosion
- Resistant to salt water and aggressive liquids

**FABRINO Produktionsgesellschaft mbH & Co. KG** | Junkersstraße 8 | 87734 Benningen
T +49 (0) 8331 92506 - 25 | F +49 (0) 8331 92506 - 36 | info@fabrino.eu | **www.fabrino.eu**